

Afterglow:

Report No.: 145355

SMT SOLUTIONS INC 52 1ST STREET HACKENSACK, NJ 07601 USA ATTN: ALBERTO LOPEZ

Date:05/29/2008

## **IDENTIFICATION SUBMITTED BY CLIENT**

DESCRIPTION: DISPOSABLE VINYL TABLE COVER, Q-TOPS

STYLE # : 2006 COLORS : WHITE

# **TEST RESULTS**

## FIRE RESISTANCE - STATE OF CALIFORNIA (NATURALS/SYNTHETICS)

Synthetics Title 19 Chapter 8 Section 1263.9 for FR chemicals applied to Std. Synthetic Interior test fabrics

#### **EVALUATION OF TEST RESULTS**

The fabric sample submitted **DOES** meet the requirements when tested, in accordance with procedure outlined in Specifications for Flame-Retardant Chemicals, Fabrics and Application concerns, California Administrative Code Title 19 (Interior Use).

			TEST RESULTS AFTERFLA (Seconds	ME		CHAR LENGTH (Inches)
	1	WARP/LENGTH	0.0			3.2
;	2	WARP/LENGTH	0.0			3.5
;	3	WARP/LENGTH	0.0			3.0
•	4	FILLING/WIDTH	0.0			3.6
	5	FILLING/WIDTH	0.0			2.0
	6	FILLING/WIDTH	0.0			3.0
Average:			0.0			3.1
OBSERVATIONS						
YES	X	NO	Localized Burning		$\square$ NO	

### FIRE RESISTANCE REQUIREMENTS: SYNTHETICS AS PER SECTION 1263.9

Afterflame shall not exceed 1.0 second for any one specimen Average char length shall not exceed 6 inches.



Report No.: 145355

# IF YOU NEED ASSISTANCE IN INTERPRETING THESE TESTS RESULTS OR IF YOU HAVE ANY QUESTIONS, PLEASE FEEL FREE TO CALL: CUSTOMER SERVICE DEPT.

## **INTERTEK LABTEST**

Erkmen Ercan Textile Technical Specialist Retail Initiative

ΕE